

HSM-V-Press-818-plus

HSM V-Press 818 plus vertical baling press

Thanks to its low transport height, the HSM V-Press 818 can be easily transported to wherever it needs to be used.



Product information

To fill the press, the upper half of the doors is folded down. Hand wheel door lock - Easy to handle thanks to counter-rotating thread for quick opening and closing. HSM TCS (Torsion Control System) for monitoring press ram movement. Automatic start of the pressing process after closing the door.

Technical Data

Order number:	6150254	Width x Depth x Height:	1700 x 1045 x 2310 mm
EAN	4026631056632	Weight:	1031 kg
Pressing power:	185 kN	Method of strapping:	vertical
Specific pressing power:	19.23 N/cm ²	Number of strappings:	4
Driving power:	4 kW	Type of consumables:	Strapping tape
Voltage / Frequency:	400 V / 50 Hz	Industry type:	Industry & Manufacturing, Print & Packaging, Logistics & Distribution, Retail
Cycle time when idling vacio:	> 7 s		
Loading height:	958 mm	Press material:	Punch waste/residue, Cardboard, Mixed paper, Plastic film, Clothing
Volume throughput at 20kg/m² (theor.):	0.1 t/h		
Loading aperture width x height:	1195 x 530 mm	Use for product line:	V-Press
Bale weight:	200 Kg		



HSM®



pbOffice - PBSA Group
78 Kyalami Boulevard, Kyalami Business Park,
Kyalami, Johannesburg, South Africa, 1684
T: +27 10 300 4893
www.pboffice.co.za