

HSM V-Press 860 L

HSM V-Press 860 L vertical baling press

The vertical baling press HSM V-Press 860 L is specially designed for the compression of opened or perforated PET/UBC bottles.



Product information

Rapid stroke technology saves time and money. To fill the press, the upper half of the doors is folded down. Reinforced press chamber and hydraulic door lock - Convenient opening and closing, no manual effort required.

Technical Data

Order number:	61 48754	Width x Depth x Height:	1 797 x 1 273 x 2 985 mm
EAN	4026631 056601	Weight:	2 220 kg
Pressing power:	434 kN	Method of strapping:	vertical
Specific pressing power:	46.37 N/cm ²	Number of strappings:	4
Driving power:	4 kW	Type of consumables:	Wire
Voltage / Frequency:	400 V / 50 Hz	Industry type:	Recycling & Disposal, Logistics & Distribution, Retail, Food & beverage industry, Industry & Manufacturing, Print & Packaging
Cycle time when idling vacio:	25 s		
Loading height:	1 115 mm	Press material:	PET bottles, aluminium beverage cans, soft packaging, Polystyrene, HDPE / LDPE hollow containers & plastic bottles, Big Bags, Clothing, Punch waste/residue, Plastic film, Mixed paper, Cardboard
Volume throughput at 20kg/m³ (theor.):	0.21 t/h		
Loading aperture width x height:	1 195 x 650 mm	Use for product line:	V-Press
Bale weight:	230 Kg		



HSM®



pbOffice - PBSA Group
78 Kyalami Boulevard, Kyalami Business Park,
Kyalami, Johannesburg, South Africa, 1684
T: +27 10 300 4893
www.pboffice.co.za